

## **Product news**

Reference: **FTD0037** Date: **April 2009** 

National Electronics Week - Stand G44 - Earls Court 2, London

16 - 18<sup>th</sup> June 2009

FTDI showcases USB 2.0 Hi-Speed devices and modules at National Electronics Week 2009

29<sup>th</sup> April 2009 – Future Technology Devices International Limited (FTDI) announced today that it will showcase its recently launched range of USB 2.0 Hi-Speed devices and development modules at National Electronics Week. These are the 5<sup>th</sup> generation of USB to UART/FIFO devices developed by the company and the ICs now offer support for applications requiring USB 2.0 480 Mb/s (Hi-Speed) interfaces.

## New ICs

The FT2232H is a dual channel device allowing one USB port to connect to two separate interfaces without a USB hub chip. Each channel may be independently configured to support UART, FIFO (synchronous and asynchronous) or, by using the Multi Purpose Synchronous Serial Engine (MPSSE), USB to I2C, SPI, JTAG or other clocked serial interfaces. Also available are MCU Emulation and bitbang modes.

The FT4232H is a quad channel device allowing one USB port to connect to four separate interfaces without a USB hub chip. Each channel may be independently configured to support UART, FIFO (asynchronous) or, by using the Multi Purpose Synchronous Serial Engine (MPSSE – available on 2 of the channels), USB to I2C,

2

SPI, JTAG or other clocked serial interfaces. Also available are MCU Emulation

and bitbang modes.

Both devices support UART transfer rates up to 12MBaud and asynchronous FIFO

speeds up to 10Mbyte/s. The synchronous FIFO mode (FT2232H only) will reach

speeds up to 25Mbyte/s and the MPSSE channels have improved on the previous

chip (FT2232D) speeds of 5.6Mbit/s to be capable of 30Mbit/s.

**New Modules** 

Two evaluation modules are available that ease the development of projects using

these new ICs. The FT2232H Hi-Speed Mini-Module and the FT4232H Mini-

Module each have one chip with a USB mini connector and two 26 way (2 rows

0.1" pitch) male header pins to allow access to all pins of the devices. Dimensions

are 36mm (L) x 30mm (W) x 12mm (H – including connector pins).

The modules are aimed at developers wishing to evaluate the devices and develop

application code but without the need to create their own PCB designs. They can

be powered from the USB host port or a separate power supply.

Drivers

As with previous generations of FTDI ICs, comprehensive and free driver support

is offered for most industry standard operating systems such as Windows, Linux

and MAC OSX. This allows developers to focus on their end application rather than

spending additional time developing drivers.

+++ends

For further information and reader enquiries:

Daniel McCaffrey, Future Technology Devices International Limited, Unit 1, 2 Seaward Place,

Centurion Business Park, Glasgow. G41 1HH

Tel: +44 (0) 141 429 2777 E-mail: sales1@ftdichip.com Fax: +44 (0) 141 429 2758 Web: www.ftdichip.com

Russ Paine, Future Technology Devices International Ltd.7235 NW Evergreen Parkway, Suite 600, Hillsboro, Oregon 97124-5803

Alex Chiang, Future Technology Devices International Limited (Taiwan), 2f, No.516, Sec.1, NeiHu Road, NeiHu District, Taipei 114, Taiwan

Tel: +886 2 8797 1330 E-mail: tw.sales1@ftdichip.com Fax: +886 2 8751 9737 Web: www.ftdichip.com

Jeff Wang, Future Technology Devices International Limited (China)

Room 408, 317 Xianxia Road, Changning District, Shanghai, 200051, P. R. China

Tel: +86 21 6235 1596 E-mail: cn.sales@ftdichip.com Fax: +86 21 6235 1595 Web: www.ftdichip.com

## For further information, text and graphics by email or to discuss feature article opportunities:

Robert Huntley, Publitek Limited, 18 Brock Street, Bath, BA1 2LW, United Kingdom

Tel: +44 (0)1225 470 000 E-mail: robert.huntley@publitek.com

Fax: +44 (0)1225 470 047 Web: www.publitek.com

## About FTDI

Future Technology Devices International (FTDI) specialise in the design and supply of silicon and software solutions for the Universal Serial Bus (USB). FTDI offer a simple route to USB migration by combining easy to implement IC devices with proven, ready to use, royalty-free USB firmware and driver software. The company's single and multi-channel USB peripheral devices come with an easy to use UART or FIFO interface. These popular devices can be used in legacy USB to RS232/RS422 converter applications or to quickly interface an MCU, PLD, or FPGA to USB. A wide range of evaluation kits and modules are available to evaluate FTDI's silicon prior to design-in.

Vinculum is FTDI's brand name for a range of USB Host / Slave Controller ICs that provide easy implementation of USB host controller functionality within products, and utilise FTDI's tried and tested embedded firmware to significantly reduce development costs and time to market.

FTDI is a fabless semiconductor company headquartered in Glasgow, UK, and has regional offices in Oregon, USA, and Taipei, Taiwan. More information is available at http://www.ftdichip.com